

ASHLAND®

SAFETY DATA SHEET

Page: 1

Revision Date: 04/03/2013

Print Date: 4/17/2013

MSDS Number: R0158700

Version: 2.0

Isoset™ WD3-A322 ADHESIVE

™ Trademark, Ashland or its subsidiaries, registered
in various countries148348

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone number	1-800-ASHLAND (1-800-274-5263)
Product name	Isoset™ WD3-A322 ADHESIVE	
	™ Trademark, Ashland or its subsidiaries, registered in various countries	
Product code	148348	

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid

NOTICE: WHILE THIS MATERIAL HAS A LOW LEVEL OF TOXICITY, GOOD INDUSTRIAL HYGIENE PRACTICES ARE ENCOURAGED TO MINIMIZE EXPOSURE.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin contact

Unlikely to cause skin irritation or injury.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions)

Symptoms

Isoset™ WD3-A322 ADHESIVE

™ Trademark, Ashland or its subsidiaries, registered in various countries148348

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

The International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP) have determined that there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite. In addition, IARC has determined that there is sufficient evidence for the carcinogenicity of quartz and cristobalite in experimental animals. Among individuals with silicosis, lung cancer occurs more frequently in those who smoke.

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

Other information

Breathing spray from emulsions may cause deposition in the lung. Respirators should be provided if engineering controls are not adequate. Residual monomer content under conditions of normal handling present no problem; however, high levels of monomer vapors can be released into workroom air when emulsions are heat cured or dried (rollers, ovens, infrared lamp, etc.). There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of immunological disorders and autoimmune diseases such as scleroderma (a disorder manifested by fibrosis of the lungs, skin and other internal organs), systemic lupus erythematosus and sarcoidosis (chronic inflammatory diseases).

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No. / Trade Secret No.	Concentration
LIMESTONE	1317-65-3	>=20-<30%
ALCOHOL ESTER POLYMER	254504001-5615	>=5-<10%
CRISTOBALITE	14464-46-1	>=0.1-<0.5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Isoset™ WD3-A322 ADHESIVE

™ Trademark, Ashland or its subsidiaries, registered in various countries148348

First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: No information available.

Treatment: No information available.

5. FIREFIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO₂), Water spray, Foam

Hazardous combustion products

calcium oxide, carbon dioxide and carbon monoxide, styrene

Precautions for fire-fighting

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. While not normally combustible, if water content is lost (as in a fire), material may release flammable vapors if exposed to high temperature. When mixed with air and exposed to ignition source, vapors can burn in open or explode if confined. Vapors may be heavier than air, may travel long distances along the ground before igniting/flashing back to vapor source. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Isoset™ WD3-A322 ADHESIVE

™ Trademark, Ashland or its subsidiaries, registered in various countries 148348

Methods for cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Other information

Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Store in a cool, dry, ventilated area. Keep from freezing.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

LIMESTONE		1317-65-3	
NIOSH	Recommended exposure limit (REL):	10 mg/m ³	Total
NIOSH	Recommended exposure limit (REL):	5 mg/m ³	Respirable.
OSHA Z1	Permissible exposure limit	5 mg/m ³	Respirable fraction.
OSHA Z1	Permissible exposure limit	15 mg/m ³	Total dust.

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Isoset™ WD3-A322 ADHESIVE

™ Trademark, Ashland or its subsidiaries, registered
in various countries148348

Wear resistant gloves (consult your safety equipment supplier).

Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Boiling point/boiling range	212 °F / 100 °C @ 1,013.33 hPa Calculated Phase Transition Liquid/Gas
pH	6.3
Flash point	> 200.1 °F / > 93.4 °C Calculated Flash Point
Evaporation rate	(>)1 Ethyl Ether
Vapour pressure	31.733 hPa @ 68 °F / 20 °C Calculated Vapor Pressure
Relative vapour density	(>)1 AIR=1
Density	1.15 - 1.25 g/cm ³ @ 77 °F / 25 °C 10.0 lb/gal @ 77 °F / 25 °C

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid

excessive heat, Freezing temperatures.

Incompatible products

Acids, ammonium salts, aluminum salts, Fluorine, reactive metals such as aluminum and magnesium,
Strong oxidizing agents

Hazardous decomposition products

calcium oxide, carbon dioxide and carbon monoxide

Hazardous reactions

Product will not undergo hazardous polymerization.

Isoset™ WD3-A322 ADHESIVE

™ Trademark, Ashland or its subsidiaries, registered
in various countries148348

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin absorption
Skin contact
Eye Contact
Ingestion

Product

Acute oral toxicity : no data available

Acute inhalation toxicity : no data available

Acute dermal toxicity : no data available

Skin corrosion/irritation : no data available

Serious eye damage/eye irritation : no data available

Respiratory or skin sensitisation : no data available

Components:

LIMESTONE:

Acute oral toxicity : LD 50 Rat: 6,450 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

no data available

Components:

no data available

Persistence and degradability

Product:

no data available

ASHLAND®

SAFETY DATA SHEET

Page: 7

Revision Date: 04/03/2013

Print Date: 4/17/2013

MSDS Number: R0158700

Version: 2.0

Isoset™ WD3-A322 ADHESIVE

™ Trademark, Ashland or its subsidiaries, registered in various countries148348

Components:

no data available

Bioaccumulative potential

Product:

no data available

Components:

no data available

Mobility in soil

Product:

no data available

Components:

no data available

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Isofet™ WD3-A322 ADHESIVE

™ Trademark, Ashland or its subsidiaries, registered in various countries 148348

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

CADMIUM
NICKEL
LEAD
ARSENIC
1,4-DIOXANE
ACETALDEHYDE
ETHYLENE OXIDE
BENZENE
CRISTOBALITE

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

CADMIUM
MERCURY
LEAD
ETHYLENE OXIDE

ASHLAND®

SAFETY DATA SHEET

Page: 9

Revision Date: 04/03/2013

Print Date: 4/17/2013

MSDS Number: R0158700

Version: 2.0

Isoset™ WD3-A322 ADHESIVE

™ Trademark, Ashland or its subsidiaries, registered in various countries148348

	BENZENE TOLUENE
--	--------------------

SARA Hazard Classification SARA 311/312 Classification

Acute Health Hazard
Chronic Health Hazard

SARA 313 Component(s)

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Notification status

US. Toxic Substances Control Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	y (positive listing)
Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)
Japan. ENCS - Existing and New Chemical Substances Inventory	y (positive listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	y (positive listing)
China. Inventory of Existing Chemical Substances	y (positive listing)

Reportable quantity - Product

US. EPA CERCLA Hazardous Substances (40 CFR 302)	125000 lbs
--------------------------------------------------	------------

Reportable quantity-Components

TOLUENE	108-88-3	1000 lbs
---------	----------	----------

	HMIS	NFPA
Health	1*	1
Flammability	1	1
Physical hazards	0	
Instability		0
Specific Hazard	--	--

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

ASHLAND®

SAFETY DATA SHEET

Page: 10

Revision Date: 04/03/2013

Print Date: 4/17/2013

MSDS Number: R0158700

Version: 2.0

Isoet™ WD3-A322 ADHESIVE

™ Trademark, Ashland or its subsidiaries, registered
in various countries148348

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System